

ORC Advanced® Pellets Technical Specification

ORC Advanced Pellets are a dust-minimizing, dry application, pelletized form of the widely-used ORC Advanced controlled-release oxygen compound.

They are designed specifically for the treatment of dissolved-phase petroleum hydrocarbons through direct application into excavations, petroleum storage tank pits, trenches and backfill.

Oxygen is released from ORC Advanced for a period of 9 to 12 months in situ.



 $CaO(OH)_2 + H_2O \rightarrow \frac{1}{2}O_2 + Ca(OH)_2 + H_2O$

Example of ORC Advanced Pellets

ORC Advanced is a formulation of calcium oxyhydroxide which, upon hydration, releases oxygen and forms simple calcium hydroxide and water.

For a list of treatable contaminants with the use of ORC Advanced, view the Range of Treatable Contaminants Guide.

Chemical Composition

- Calcium Oxyhydroxide
- Calcium Hydroxide
- Monopotassium Phosphate
- Ammonium Phosphate Dibasic

Properties

- Pellet size: 3-10 mm
- Contains micro-nutrients such as nitrogen, phosphorous, and potassium (N,P,K) which can be beneficial to aerobic biodegradation processes



ORC Advanced® Pellets Technical Specification

Storage and Handling Guidelines

Storage

Store in a cool, dry place out of direct sunlight

Store in original tightly closed container

Store in a well-ventilated place

Do not store near combustible materials

Store away from incompatible materials

Provide appropriate exhaust ventilation in places where dust is formed

Handling

Minimize dust generation and accumulation

Keep away from heat

Routine housekeeping should be instituted to ensure that dust does not accumulate on surfaces

Observe good industrial hygiene practices

Take precaution to avoid mixing with combustibles

Keep away from clothing and other combustible materials

Avoid contact with water and moisture

Avoid contact with eyes, skin, and clothing

Avoid prolonged exposure

Wear appropriate personal protective equipment

Applications

- In situ or ex situ out of the bag
- Direct application into open excavations, petroleum storage tank pits and trenches
- Direct application to contaminated backfill or contaminated soils
- Ex situ biopile applications (requires a source of hydration)

Health and Safety

Wash thoroughly after handling. Wear protective gloves, eye protection, and face protection. Please review the Material Safety Data Sheet for additional storage, usage, and handling requirements here: <u>ORC Advanced SDS</u>.

