

PlumeStop® Liquid Activated Carbon™ Technical Description

PlumeStop Liquid Activated Carbon is an innovative groundwater remediation technology designed to rapidly remove and permanently degrade groundwater contaminants. PlumeStop is composed of very fine particles of activated carbon (1-2 μ m) suspended in water through the use of unique organic polymer dispersion chemistry. Once in the subsurface, the material behaves as a colloidal biomatrix, binding to the aquifer matrix, rapidly removing contaminants from groundwater, and expediting permanent contaminant biodegradation.

This unique remediation technology accomplishes treatment with the use of highly dispersible, fast-acting, sorption-based technology, capturing and concentrating dissolved-phase contaminants within its matrix-like structure. Once contaminants are sorbed onto the regenerative matrix, biodegradation processes achieve complete remediation at an accelerated rate.



Distribution of PlumeStop in water

To see a list of treatable contaminants with the use of PlumeStop, view the Range of Treatable Contaminants Guide.

Chemical Composition

- Water CAS# 7732-18-5
- Colloidal Activated Carbon ≤2.5 CAS# µm 7440-44-0
- Proprietary Additives

Properties

- Physical state: Liquid
- Form: Aqueous suspension
- Color: Black
- Odor: Odorless
- pH: 8 10

Storage and Handling Guidelines

Storage

Store in original tightly closed container

Store away from incompatible materials

Protect from freezing

Handling

Avoid contact with skin and eyes

Avoid prolonged exposure

Observe good industrial hygiene practices

Wash thoroughly after handling

Wear appropriate personal protective equipment



PlumeStop® Liquid Activated Carbon™ Technical Description

Applications

PlumeStop is easily applied into the subsurface through gravity-feed or low-pressure injection.

Health and Safety

Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Please review the Material Safety Data Sheet for additional storage, usage, and handling requirements here: <u>PlumeStop SDS</u>.



www.regenesis.com