


PersulfOx[®] Technical Description

PersulfOx is an *In Situ* Chemical Oxidation (ISCO) reagent that destroys organic contaminants found in groundwater and soil through powerful, yet controlled, chemical reactions. A sodium persulfate-based technology (figure 1), PersulfOx employs a patented catalyst to enhance the oxidative destruction of both hydrocarbons and chlorinated contaminants in the subsurface.

Typically, sodium persulfate is activated with the addition of heat, chelated metals, hydrogen peroxide, or base in order to generate sulfate radicals. These activation processes are inherently complex, costly and can pose additional health and safety risks. In comparison, PersulfOx is a relatively safe and easy-to-use ISCO agent with a built-in catalyst which activates the persulfate component, generating contaminant-destroying free radicals without the need for the addition of a separate activator. The equation below shows the net complete oxidation of toluene, a constituent of gasoline, by PersulfOx:



Example of PersulfOx



For a list of treatable contaminants with the use of PersulfOx, view the [Range of Treatable Contaminants Guide](#)

Chemical Composition

- Sodium Persulfate - CAS #7775-27-1
- Sodium Silicate - CAS #1344-09-8

Properties

- pH - 7 to 11.5 at 25°C
- Appearance - White, free-flowing powder, clear to cloudy when mixed with water
- Odor - Not detectable
- Vapor Pressure - None
- Chemical Hazard Classification - Class 5.1 Oxidizer

Storage and Handling Guidelines

Storage

- Store locked up
- Keep away from heat
- Store in a cool, dry place out of direct sunlight

Handling

- Minimize dust generation and accumulation
- Routine housekeeping should be instituted to ensure that dust does not accumulate on surfaces

PersulfOx® Technical Description

Storage (continued)

- Store in original tightly closed container
- Store in a well-ventilated place
- Do not store near combustible materials
- Store away from incompatible materials
- Recommended to store at less than 40°C
- Provide appropriate exhaust ventilation in places where dust is formed

Handling (continued)

- Avoid mixing with combustibles
- Avoid contamination
- Keep away from clothing and other combustible materials
- Wear appropriate personal protective equipment
- Avoid breathing dust
- Avoid contact with eyes, skin, and clothing
- Avoid prolonged exposure
- Do not taste or swallow
- When using, do not eat, drink or smoke
- Wear appropriate personal protective equipment
- Wash hands thoroughly after handling
- Observe good industrial hygiene practices

Applications

- PersulfOx is mixed with water at a rate of 5% to 20% prior to application.
- For most applications, REGENESIS suggests a 10-15% solution. The resulting mixture has viscosity similar to water.
- Injects into formation through direct push injection points, injection wells or other injection delivery systems.

Application instructions for this product are contained here [PersulfOx Application Instructions](#).

Health and Safety

Material is relatively safe to handle; however, avoid contact with eyes, skin and clothing. OSHA Level D personal protection equipment including: vinyl or rubber gloves, eye protection, and dust mask are recommended when handling this product. Please review the Material Safety Data Sheet for additional storage, usage, and handling requirements here: [PersulfOx SDS](#).



www.regenesis.com

Corporate Headquarters
1011 Calle Sombra, San Clemente CA 92673
949.366.8000

European Office
Cambridge House, Henry Street,
Bath BA1 1BT, United Kingdom