

Successful Pilot Test Results in Full-Scale Treatment of Large BTEX Plume

CASE SUMMARY

Refueling Station – Algonquin, IL

Leaking underground storage tanks at a refueling station resulted in a benzene, toluene, ethylbenzene and xylene (BTEX) plume in the underlying sand/gravel aquifer. The plume covered 1-acre and extended 390 feet downgradient from the source area, with a total BTEX concentration exceeding 24,000 parts per billion (ppb). In an effort to mitigate the source, 795 cubic yards of contaminated soil was excavated; however, further groundwater monitoring revealed that BTEX concentrations still exceeded the Illinois EPA cleanup levels. To address the remaining contamination and reduce concentrations to the state cleanup goal, a remediation plan was implemented using Oxygen Release Compound (ORC®) and ORC Advanced®.

REMEDIATION APPROACH


The remediation objective was to reduce petroleum hydrocarbon contamination, mainly benzene, to the state cleanup goal. A pilot test was performed using ORC to observe the effectiveness of reducing BTEX concentrations. Successful reduction was achieved within 4 months and a full-scale application was implemented. The full-scale application was focused near the source area as well as within the mid-plume area (near MW-7 & MW-8). Two applications followed within the mid- and lower plume areas to continue BTEX reduction.

Table 1. ORC and ORC Advanced Application Details

| | Product | Pounds Applied | Location of Injection |
|----------------|------------------|----------------|--|
| September 2000 | ORC (Pilot) | 300 | Upper Plume (MW-4) |
| January 2002 | ORC (Full Scale) | 8250 | Upper Plume (MW-4) Mid-Plume (MW-7) |
| December 2002 | ORC | 8250 | Mid-Plume (MW-7) |
| July 2004 | ORC | 7525 | Mid-Plume (MW-7) |
| 2004 | Advanced | | Lower Plume (MW-10) |

- f **Application Type:** Grid & Barrier Application
- f **Soil Type:** Clay above Sand/Gravel
- f **Groundwater Velocity:** 0.25 ft/day
- f **Treatment Area:** 43,500 ft²
- f **Injection Spacing:** 10–20 feet
- f **Product Cost:** \$171,600

Figure 1. BTEX Plume Location







RESULTS

| Contaminant | Pilot Test | | Full-Scale Implementation | |
|--------------|------------|----------|---------------------------|----------|
| | Pre-ORC | Post-ORC | Pre-ORC | Post-ORC |
| Benzene | 352 | 42.6 | 2,390 | ND |
| Toluene | 17.1 | ND | 33.2 | ND |
| Ethylbenzene | 383 | 47.3 | 962 | ND |
| Xylenes | 704 | 33.6 | 4,000 | ND |

Concentrations vs. Time



A high groundwater event resulted in re-contamination of the aquifer due to significant smear zone contamination near MW-4. October 2001 shows an increase in BTEX by more than 4,300 ppb. The full scale application in January 2002 reduced concentrations to non-detect.



A continuous decrease in BTEX resulted in an overall contaminant mass reduction of 85%. The multiple ORC applications were successful at sustaining an aerobic environment to facilitate bioremediation within the plume.

| Monitoring Well | Percent Reduction in Benzene | Final Benzene (ppb) |
|-----------------|------------------------------|---------------------|
| MW-5 | 96% | 25.6 |
| MW-7 | 99% | 8.1 |
| MW-9 | 98% | 67.8 |
| MW-10* | 96% | <5.0 |
| MW-12 | 78% | 39.9 |
| MW-14 | 77% | 45.3 |

*Well MW-10 has reached the cleanup goal of 5 ppb

Five of the ten contaminated monitoring wells achieved the remedial objective for benzene as well as all other contaminants following the ORC and ORC Advanced injection. Benzene reduction for those wells that have not yet achieved the cleanup goal are listed in Table 3. Overall, a benzene mass reduction of over 95% was achieved. It is expected that the remaining contaminant concentrations will reach cleanup goals as monitoring continues.

CONTACT

Barry Poling
 RegenesiS
 Central U.S. Regional Manager
 812-923-7999 | bpoling@regenesiS.com

Consultant contact information available upon request. Please contact the RegenesiS representative listed above.