

PlumeStop® Liquid Activated Carbon™ Technical Description

PlumeStop® Liquid Activated Carbon™ is an innovative groundwater remediation technology designed to rapidly remove and permanently degrade groundwater contaminants. PlumeStop is composed of very fine particles of activated carbon (1-2µm) suspended in water through the use of unique organic polymer dispersion chemistry. Once in the subsurface, the material behaves as a colloidal biomatrix, binding to the aquifer matrix, rapidly removing contaminants from groundwater, and promoting permanent contaminant biodegradation.

This unique remediation technology accomplishes treatment with the use of highly dispersible, fast-acting, sorption-based technology, capturing and concentrating dissolved-phase contaminants within its matrix-like structure. Once contaminants are sorbed onto the regenerative matrix, biodegradation processes achieve complete remediation.



Distribution of PlumeStop in water

To see a list of treatable contaminants with the use of PlumeStop, view the [Range of Treatable Contaminants Guide](#).

Chemical Composition

- Water – CAS# 7732-18-5
- Colloidal Activated Carbon ≤2,5 – CAS# µm 7440-44-0
- Proprietary Additives

Properties

- Physical state: Liquid
- Form: Aqueous suspension
- Color: Black
- Odor: Odorless
- pH: 8 - 10

Storage and Handling Guidelines

Storage
Store in original tightly closed container
Store away from incompatible materials
Protect from freezing

Handling
Avoid contact with skin and eyes
Avoid prolonged exposure
Observe good industrial hygiene practices
Wash thoroughly after handling
Wear appropriate personal protective equipment

PlumeStop® Liquid Activated Carbon™ Technical Description

Applications

PlumeStop is easily applied into the subsurface through gravity-feed or low-pressure injection.

Health and Safety

Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Please review the Material Safety Data Sheet for additional storage, usage, and handling requirements here: [PlumeStop SDS](#).

